Technical Data Sheet

Release Date: Dec, 2024, NO.: REZUX-AD-20251224-01E

Enfinol® AD632

Version: 4

Performance Overview

- Enfinol® AD632 is a non-ionic, no-solvent, polyurethane thickener provided in solution form. It is used to build high shear viscosity in water-based coatings, enhance the leveling of the paint film, and improve the fullness of the coating.

Product Features

- Good levelling properties.
- Beneficial to form uniform film thickness and better film fullness
- Easy to handle with a wide pH compatibility range.

Physical Property

Product Specifications

Appearance:	White liquid.
Solids (%):	20.0
pH:	6.5
Specific gravity（g/ml）:	1.04

Application

- Widely used in coatings, inks, and other applications.

Use Method

- Recommended addition: 0.1 - 5.0%. The optimal amount should be determined through a series of tests.
- Added during the grinding and paint mixing stages.

REZUX

Packaging & Storage

- 20kg、200kg & 1000 kg/Barrel
- Use the original container to store in a cool, dry environment, avoid freezing
- Shelf life of 12 months from the date of production.

Service Restrictions

- This product has not been tested nor has it been specifically stated that it is suitable for medical or pharmaceutical use. It may not be used for human injection or consumption.

Limited Warranty Information - Please read carefully

- The content of this product data sheet is based on the products owned by my company, and is provided for reference only.
- Due to the numerous formulations, production, and application conditions, customers should pre-test the adaptability of my company's products before using them to determine their performance, efficiency, and safety.
- The suggestions we provide shall not be considered as a cause of any patent infringement. The sole responsibility of our company is to refund the money or exchange it for a product with same value.
- Welcome to visit our website, **www.rezux.com**, for more information.