Technical Data Sheet

Release Date: Dec, 2025, NO.: REZUX-AD-20251224-05E

Enfinol® AD620

Version: 2

Performance Overview

- Enfinol® AD620 is a low-cost, high-performance, hydrophobic modified, alkali-soluble, anionic associative thickener, designed to build up medium-shear viscosity in interior/exterior flat latex paints. It offers the formulation of paints with excellent resistance to roller spattering with better film building and levelling than conventional thickeners.

Product Features

- Good film building and levellig ability.
- Excellent hiding power with good application results.
- Offering higher cost-effectiveness and better roller spattering resistance.

Physical Property

Products Typical Data

Appearance:	Opaque, white to off-white liquid.
Solids (%):	30
Density (g/ml):	1.05
pH:	2.7
Viscosity (25℃, cps):	＜350

Application

- Widely used in the waterborne coatings.

Use Method

- Recommended addition: 0.1 - 1.0%. Add during the paint mixing stage.
- The optimal amount should be determined through a series of tests.

Packaging & Storage

- 20kg、200kg & 1000 kg/Barrel
- Shelf life of 12 months from the date of production.

Service Restrictions

- This product has not been tested nor has it been specifically stated that it is suitable for medical or pharmaceutical use. It may not be used for human injection or consumption.

Limited Warranty Information - Please read carefully

- The content of this product data sheet is based on the products owned by my company, and is provided for reference only.
- Due to the numerous formulations, production, and application conditions, customers should pre-test the adaptability of my company's products before using them to determine their performance, efficiency, and safety.
- The suggestions we provide shall not be considered as a cause of any patent infringement. The sole responsibility of our company is to refund the money or exchange it for a product with same value.
- Welcome to visit our website, **www.rezux.com**, for more information.